

ECT002 TWO DUPLEX CHANNEL DATA FM OPTICAL LINK



ECT002 system provides two duplex channel high performance link for bidirectional transmitting data signals over a fiber optic cable. The system features quality transmission of data signals with data rates DC – 10 Mb/sec.

ECT002 utilizes high-speed frequency modulation and very low noise transmission technology to assure high accuracy and stability.

ORDERING INFORMATION

002E-DXF-MYZ

E = **M** for multimode receiver and 850 nm transmitter
 = **S** for single mode receiver and 1310 nm transmitter
 = **S(15)** for single mode receiver and 1550 nm transmitter
 = **S(15)D** for single mode DFB 1550 nm transmitter
F = **1** for TTL/CMOS data format;
 3 for RS-232 data format;
 4 for RS-422 data format;
 5 for RS-485 data format;
 7 for 20 mA current loop data format;
 9 for contact closure data format.

Y = **1, 2** number of fibers

Z = **ST, SC, FC** for optical connectors

Note: The specifications are subject to change without notice.

FEATURES

- ❑ High Speed Duplex Data Transmission, DC – 10 Mb/sec.
- ❑ Multimode and Single mode Versions
- ❑ Isolates EMI, RFI, Ground Loops
- ❑ Surface Mount Technology
- ❑ Power and Signal Status Indicators
- ❑ Dry contact lost link alarm
- ❑ 12 VDC or 24 VAC Power Supply

Operating Wavelength	850 nm	1310/1550 nm
Optical Core Diameter	50μ/62.5μ	8/10μ
Optical Power Source	VCSEL	Laser
Optical Power Output*	-4 dBm	-4 dBm
Receiver Sensitivity	-30 dBm	-34 dBm
Receiver Sensitivity**	-28 dBm	-33 dBm
Optical Connectors	ST, SC	ST, SC, FC

*with +/- 1 dBm variation;

** for configurations with internal WDM.

Channel Capacity	2 Duplex Data Channel
Data Rate	DC-10 Mb/sec for TTL & RS-422 DC-200 Kb/sec for RS-232, RS-485 & 20 mA current loop
Data Connector	RJ45
Power Requirements	11 – 14 VDC @ 200 mA 21 – 27 VAC @ 200mA
Power Connector	Terminal Block with Plug, 3 pos.
Operating Temperature	-20°C to +70°C (-4°F to +158°F)
Dimensions:	6.86" x 4.95" 1.4" 172mm x 126mm x 36mm

