

ECT010(2-8) TWO / EIGHT CHANNEL TTL/CMOS DATA OPTICAL LINK



| |
|-------|
| Data |
| 2 / 8 |
| → |

ECT010(2-8) system provides two or eight channel high performance unidirectional link for transmitting TTL/CMOS data signals over a fiber optic cable.

The system features quality transmission of data signals with data rates DC – 5 Mb/sec. ECT010(2-8) utilizes high-speed frequency modulation and very low noise transmission technology to assure high accuracy and stability.

FEATURES

- ❑ High Speed Data Transmission, DC – 5 Mb/sec
- ❑ Multimode and Singlemode Versions
- ❑ Isolates EMI, RFI, Ground Loops
- ❑ Surface Mount Technology
- ❑ Power and Signal Status Indicators

| Operating Wavelength | 850 nm | 1300 nm | 1310/1550nm |
|-----------------------|-----------|---------|-------------|
| Optical Core Diameter | 50μ/62.5μ | | 8/10μ |
| Optical Power Source | VCSEL | LED | Laser |
| Optical Power Output* | -3 dBm | -14 dBm | -4 dBm |
| Receiver Sensitivity | -30 dBm | -34 dBm | -36 dBm |
| Optical Connectors | ST, SC | | ST, SC, FC |

* with +/- 1 dBm variation; higher power laser sources are available per special request.

| | |
|---|--|
| Channel Capacity | 2Ch. - for standalone module 8Ch. - for rack card or standalone card-module |
| Data Rate | DC – 5 Mb/sec |
| Data Input Impedance | 22 kOhm unbalanced |
| Power Requirements: | |
| 2Ch. Module | 11 - 14 VDC @ 200 mA 21 - 27 VAC @ 150 mA |
| 8Ch. Card / Module | 11 - 14 VDC @ 400 mA |
| Operating Temperature | -20°C to +70°C (-4°F to +158°F) |
| Dimensions: | |
| 2Ch. Module | 4.17"(106mm) x 3.65"(93mm) x 1.1"(28mm) |
| 8Ch. Card / Module (w/o connectors) | 11.6"(270mm) x 5.2"(132mm) x 1.05"(27mm) |
| 8Ch. Card / Module (with connectors) | 12.5"(318mm) x 5.2"(133mm) x 1.05"(27mm) |



ORDERING INFORMATION

010E-DT2-MYZ - Data Transmitter 2Ch. Module
010E-DR2-MYZ - Data Receiver 2Ch. Module
010E-4/DT2-MYZ - Data Transmitter 8Ch. Module
010E-4/DR2-MYZ - Data Receiver 8Ch. Module
010E-4/DT2-CYZ - Data Transmitter 8Ch. Card*
010E-4/DR2-CYZ - Data Receiver 8Ch. Card*

E = **M** for multimode 850 nm
= **M(13)** for multimode 1300 nm
= **S** for single mode receiver or 1310 nm transmitter
= **SP** for single mode high power (≥ 0 dBm) 1310 nm transmitter
= **SPD** for single mode high power (≥ 0 dBm) 1310 nm / DFB transmitter
= **S(15)** for single mode 1550 nm transmitter
= **S(15)P** for single mode high power (≥ 0 dBm) 1550 nm transmitter
= **S(15)D** for single mode 1550 nm / DFB transmitter
= **S(15)PD** for high power (≥ 0 dBm) 1550 nm / DFB transmitter
= **S(W)** for single mode CWDM / DFB transmitter
= **S(W)P** for high power (≥ 0 dBm) CWDM / DFB transmitter

CWDM wavelength (**W**): **14.7**(1470 nm), **14.9**(1490 nm), **15.1**(1510 nm), **15.3**(1530 nm),
15.5(1550 nm), **15.7**(1570nm), **15.9**(1590 nm), **16.1**(1610 nm).

Y = **1** number of fibers for standalone module
= **1**(with 4ch. CWDM), **2**(with 2 x 2ch. WDM), **4** number of fibers for 4 channel module or rack card
Z = **ST**, **SC**, **FC** for optical connectors

**compatible with USR type chassis.*

Note: The specifications are subject to change without notice.



Elcommtech Corp. 2620 Ocean Parkway, Suite 4H, Brooklyn, NY 11235
Tel (718) 743-2869 • Fax (718)648-3642 • E-mail sales@elcommtech.com
<http://www.elcommtech.com>