

ECT088 T1/E1 DATA OPTICAL LINK



FEATURES

- ❑ High Speed Duplex T1 or E1 Data Transmission
- ❑ AMI, B8ZS and HDB3 Data Formats
- ❑ Multimode and Singlemode Versions
- ❑ Isolates EMI, RFI, Ground Loops
- ❑ Surface Mount Technology
- ❑ Power and Signal Status Indicators
- ❑ 12 VDC or 24 VAC Power Supply

ECT088 system provides high performance duplex link for transmitting T1 or E1 data signal over a fiber optic cable.

The system features quality transmission of data signals with data rates 1.544 Mb/sec (T1) and 2.048 Mb/sec (E1).

ECT088 utilizes high-speed frequency modulation and very low noise transmission technology to assure high accuracy and stability.

Operating Wavelength	850 nm	1300 nm	1310/1550nm
Optical Core Diameter	50μ/62.5μ		8/10μ
Optical Power Source	VCSEL	LED	Laser
Optical Power Output*	-3 dBm	-14 dBm	-4 dBm
Receiver Sensitivity	-30 dBm	-34 dBm	-36 dBm
Receiver Sensitivity**	-29 dBm	-33 dBm	-35 dBm
Optical Connectors	ST, SC		ST, SC, FC

* with +/- 1 dBm variation; higher power laser sources are available per special request;

** for one-fiber configuration with internal WDM.

ORDERING INFORMATION

088E-N/DX-XYZ

- E = M for multimode
- = M(13) for multimode 1300nm
- = S for single mode receiver or 1310nm transmitter
- = SP for high power (0 dBm) 1310nm transmitter option
- = S(15) for single mode 1550nm transmitter
- = S(15)P for high power (0 dBm) 1550nm transmitter option
- N = 2 for 2ch. rack card only
- X = M for standalone module
- = C for rack card*
- Y = 1, 2 or 4 (rack card only) for number of fibers
- Z = ST, SC, FC for optical connectors

*compatible with USR type chassis

Channel Capacity	1Ch. - for standalone module 2Ch. - for rack card
Data Interface	T1 or E1
Data Rate	1.544 or 2.048 Mb/sec
Data Input Impedance	120Ω balanced or 75 unbalanced
Power Requirements:	
Module	11 - 14 VDC @ 200 mA 21 - 27 VAC @ 150 mA
Card	11 - 14 VDC @ 400 mA
Operating Temperature	-20°C to +70°C (-4°F to +158°F)
Dimensions:	
Module	6.86" (172mm) x 4.95" (126mm) x 1.4" (36mm)
Card (w/o connectors)	11.6" (270mm) x 5.2" (132mm) x 1.05" (27mm)
Card (with connectors)	12.5" (318mm) x 5.2" (133mm) x 1.05" (27mm)

Note: The specifications are subject to change without notice.



Elcommtech Corp. 2620 Ocean Parkway, Suite 4H, Brooklyn, NY 11235
 Tel (718) 743-2869 • Fax (718) 648-3642 • E-mail sales@elcommtech.com
<http://www.elcommtech.com>