


## ECT100 ONE CHANNEL VIDEO FM OPTICAL LINK



The ECT100 system provides high performance link for unidirectional transmission of composite video signal over a fiber optic cable. The system features CCTV professional video quality and guarantees quality transmission of video signals with maximum bandwidth up to 30 MHz.

The ECT100 utilizes linear frequency modulation and very low noise transmission technology to assure high quality and stability.

### ORDERING INFORMATION

100EH-VT-M1Z – Video transmitter module  
 100EH-VR-M1Z – Video receiver module

**E** = **M** for multimode 850 nm  
 = **S** for single mode receiver and 1310 nm transmitter  
 = **S(15)** for single mode 1550 nm transmitter  
 = **SD, S(15)D** for DFB lasers option transmitter  
**H** = For higher 30 MHz bandwidth only

**Z** = **ST, FC** for optical connectors

**Note:** The specifications are subject to change without notice

### FEATURES

- ❑ CCTV Professional Video Quality
- ❑ Balanced Video Input
- ❑ Video Bandwidth 18 MHz
- ❑ Compatible with NTSC, PAL and SECAM Transmission
- ❑ Multimode and Single Mode Versions
- ❑ Power and Signal Status Indicators

<b>Operating Wavelength</b>	850 nm	1310/1550nm
<b>Optical Core Diameter</b>	<b>50μ/62.5μ</b>	<b>8/10μ</b>
<b>Optical Power Source</b>	VCSEL	Laser
<b>Optical Power Output*</b>	-4 dBm	-6 dBm
<b>Receiver Sensitivity</b>	-31 dBm	-34 dBm
<b>Optical Connectors</b>	ST, SC	FC, ST, SC

\*with +/- 1 dBm variation; measured with multimode 62.5μ or single mode 8-10μ 1metre patch cord.

<b>Video Bandwidth @ 3 dB*</b>	10Hz - 18 MHz
<b>Video Input</b>	75 Ohm universal: balanced or unbalanced
<b>Video Input/Output Level</b>	NTSC: 1.0 V p-p, PAL: 1.3 V p-p
<b>Signal-to-Noise Ratio**</b>	62 dB
<b>Differential Gain</b>	< 4%
<b>Differential Phase</b>	< 4°
<b>Field Tilt</b>	< 2%
<b>Luminance Non-Linearity</b>	< 4%
<b>Power Requirements</b>	11 - 14 VDC @ 150mA, 21 - 27 VAC @ 100mA
<b>Operating Temperature</b>	-20°C to +70°C (-4°F to +158°F)
<b>Dimensions:</b>	
<b>Transmitter***</b>	3.20"(81mm) x 3.72"(95mm) x 1.1"(28mm)
<b>Receiver***</b>	4.17"(106mm) x 3.65"(93mm) x 1.1"(28mm)

\*higher 30 MHz bandwidth available;

\*\*measured as per RS-250C @ 100m for multimode and 1km for single mode optical cable;

\*\*\*measured without optical & power connectors.

