

ECT114H

ONE VIDEO WITH ONE TTL/CMOS & ONE RS-422 DATA CHANNELS DIGITAL OPTICAL LINK



Video	Data
1	2
→	↔

ECT114H system provides high performance link for transmitting unidirectional composite video channel along with one TTL/CMOS & one RS-422 bi-directional data channels over one or two fibers. The system features broadcast video quality providing 10-bit video processing with uncompressed digital transmission.

ECT114H system utilizes high speed analog-to-digital and digital-to-analog conversion with 10-bit resolution, digital signal processing, time division multiplexing, fibre optic transmission at a data rate of up to 1400 Mbit/sec and high speed data transfer capability.

ORDERING INFORMATION

114HE-VT/DXN-MYZ – video TX/data TRX module
 114HE-VR/DXN-MYZ – video RX/data TRX module
 TX - transmitter, RX – receiver, TRX - transceiver

E = **M** for multimode 850 nm/TX
 = **S** for single mode 1310 nm/TX
 = **S(15)** for single mode 1550 nm/TX

N = **5, 10*** for data rate maximum in Mb/sec**
Y = **1** for one fiber system
 = **2** for dual fiber system

Z = **ST, FC, SC** for optical connectors

*for one data channel only;

**specified by customer.

Note: The specifications are subject to change without notice.

FEATURES

- ❑ Broadcast Video Quality
- ❑ Compatible with NTSC, PAL and SECAM Transmission
- ❑ High Speed Duplex TTL/CMOS & RS-422 Data Ports
- ❑ Multimode and Singlemode Versions
- ❑ Power and Signal Status Indicators

Operating Wavelength	850 nm	850/1300 nm	1310/1550 nm
Optical Core Diameter	50µ/62.5µ		8/10µ
Optical Power Source	VCSEL	LED	Laser
Optical Power Output*	-3 dBm	-14 dBm	-3 dBm
Video Receiver Sensitivity	-30 dBm		-33 dBm
Video Receiver Sensitivity**	-28 dBm		-31 dBm
Data Receiver Sensitivity	-33 dBm	-36 dBm	-36 dBm
Data Receiver Sensitivity**	-31 dBm	-34 dBm	-34 dBm
Optical Connectors	ST, SC		ST, SC, FC

* with +/- 1 dBm variation; higher power laser sources are available per special request;

** for one-fiber configuration with internal WDM.

Video Bandwidth @ 2 dB*	10 MHz
Video Conversion Resolution	10 bit
Video Input	75 Ohm balanced
Video Output	75 Ohm unbalanced
Video Input/Output Level	NTSC: 1.0 V p-p, PAL: 1.3 V p-p
Signal-to-Noise Ratio**	64 dB
Differential Gain	< 0.5 %
Differential Phase	< 0.5 °
Field Tilt	< 0.5 %
Luminance Non-Linearity	< 0.5 %
Data Interface	TTL/CMOS & RS-422
Data Rate	DC - 2.5 Mb/sec DC - 5 Mb/sec, 10 Mb/sec***
Bit Error Rate	10 ⁻⁹
Power Requirements	11 - 14 VDC @ 350mA 21 - 27 VAC @ 250mA
Operating Temperature	-30°C to +70°C (-22°F to +158°F)
Module Dimensions	6.7"(170mm) x 4.95"(126mm) x 1.32"(34mm)

* higher video bandwidth (up to 26 MHz) is available per special request;

** measured as per RS-250C @ 1km for single mode optical cable;

*** available per special request; 10 Mb/sec - for one data channel only.



Elcommtech Corp. 2620 Ocean Parkway, Suite 4H, Brooklyn, NY 11235
 Tel (718) 743-2869 • Fax (718)648-3642 • E-mail sales@elcommtech.com
<http://www.elcommtech.com>