

# ECT100 SERIES

## ECT155H DIGITAL VIDEO WITH RS-485 DATA CHANNEL



Video	Data
1	1
→	↔

ECT155H system provides high performance link for transmitting unidirectional composite video channel along with one RS-485 data channel over one or two fibers. The system features broadcast video quality providing 10-bit video processing with uncompressed digital transmission. ECT155H utilizes high speed analog-to-digital and digital-to-analog conversion with 10-bit resolution, digital signal processing, time division multiplexing, fibre optic transmission at a data rate of up to 1400 Mbit/sec and high speed RS-485 data transfer capability.

### ORDERING INFORMATION

155HE-VT/DXN-MYZ – video Tx/data TRx module  
 155HE-VR/DXN-MYZ – video Rx/data TRx module  
 Tx - transmitter, Rx – receiver, TRx - transceiver

E = M for multimode 1 fiber or 850nm/2 fiber  
 = S for singlemode 1 fiber or 1310nm/2 fiber  
 = S(15) for singlemode 1550nm/2 fiber

N = 2, 4 for number of wires

Y = 1 for one fiber system  
 = 2 for dual fiber system

Z = ST, FC, SC for optical connectors

### FEATURES

- ❑ Broadcast Video Quality
- ❑ Compatible with NTSC, PAL and SECAM Transmission
- ❑ High Speed RS-485 Data Port
- ❑ Two and Four Wire Interface
- ❑ Multimode and Singlemode Versions
- ❑ Power and Signal Status Indicators

Operating Wavelength	850 nm Video	1300 nm Data	1310/1550nm Video/Data
Optical Core Diameter	50µ/62.5µ		8/10µ
Optical Power Source	VCSEL	LED	Laser
Optical Power Output*	-3 dBm	-14 dBm	-5 dBm
Receiver Sensitivity	-30 dBm	-35 dBm	-35 dBm
Receiver Sensitivity**	-28 dBm	-33 dBm	-33 dBm
Optical Connectors	ST, SC		FC, ST, SC

\* with +/- 1 dBm variation; higher power laser sources are available per special request;

\*\* for one-fiber configuration with internal WDM.

Video Bandwidth @1dB*	6.5 MHz
Video Conversion Resolution	10 bit
Video Input	75 Ohm balanced
Video Output	75 Ohm unbalanced
Video Input/Output Level	NTSC: 1.0 V p-p, PAL: 1.3 V p-p
Signal-to-Noise Ratio**	64 dB
Differential Gain	< 0.5 %
Differential Phase	< 0.5 °
Field Tilt	< 0.5 %
Luminance Non-Linearity	< 0.5 %
Data Interface	RS-485
Data Rate	Up to 1.6 Mb/s
Bit Error Rate	10 <sup>-9</sup>
Power Requirements	11 - 14 VAC/VDC @ 350mA 21 - 27VAC @ 250mA
Operating Temperature	-30°C to +70°C (-22°F to +158°F)
Module Dimensions	6.7"(170mm) x 4.95"(126mm) x 1.32"(34mm)

\* higher video bandwidth (up to 25 MHz) is available per special request;

\*\* measured as per RS-250C @ 4km, 8-9µ cable;



Elcommtech Corp. 2620 Ocean Parkway, Suite 4H, Brooklyn, NY 11235  
 Tel (718) 743-2869 • Fax (718)648-3642 • E-mail contact@elcommtech.com  
<http://www.elcommtech.com>