


ECT299 DUAL VIDEO WITH FOUR DUPLEX CONTACT CLOSURE DATA CHANNELS FM OPTICAL RECEIVER



Video	Data
2	4
→	↔

ECT299 system provides high performance link for receiving of two unidirectional composite video channels along with four bi-directional contact closure data channels over two or four fibers. The system features CCTV professional video quality and high speed contact closure data transfer capability. ECT299 utilizes linear frequency demodulation and very low noise reception technology to assure high quality and stability.

ORDERING INFORMATION

299E-VR/DX-CYZ – 2 x Video RX/cont. closure data TRX card
 299E-VR/DX-MYZ – 2 x Video RX/cont. closure data TRX module
 RX – receiver, TRX - transceiver

- E** = **M** for multimode 850 nm/TX
- = **M(13)** for multimode 1300 nm/TX
- = **S** for single mode 1310 nm/TX
- = **S(15)** for single mode 1550 nm/TX
- Y** = **2** for single fiber system (1 fiber per channel)
- = **4** for dual fiber system (2 fiber per channel)
- Z** = **ST, SC, FC** for optical connectors

FEATURES

- ❑ CCTV Professional Video Quality
- ❑ Compatible with NTSC, PAL and SECAM Transmission
- ❑ High Speed Contact Closure Data Ports
- ❑ Multimode and Singlemode Versions
- ❑ Power and Signal Status Indicators

Operating Wavelength	850 nm	1300 nm	1310/1550 nm
Optical Core Diameter	50μ/62.5μ		8/10μ
Optical Power Source	VCSEL	LED	Laser
Optical Power Output*	-7 dBm	-14 dBm	-8 dBm
Video & Data Receiver Sensitivity	-30 dBm	-34 dBm	-36 dBm
Video & Data Receiver Sensitivity**	-29 dBm	-33 dBm	-35 dBm
Optical Connectors	ST, SC		FC, ST, SC

* with +/- 1 dBm variation; higher power laser sources are available per special request;

** for one-fiber configuration with internal WDM

Video Bandwidth @ 3 dB	7 MHz
Video Output	75 Ohm unbalanced
Video Output Level	NTSC: 1.0 V p., PAL: 1.3 V p. (+/-10%)
Signal-to-Noise Ratio	62 dB*
Differential Gain	< 4 %
Differential Phase	< 4 °
Field Tilt	< 2 %
Luminance Non-Linearity	< 4 %
Data Interface Input	Dry Contact, TTL/CMOS
Data Interface Output	Dry Contact @ load 24VAC or 30VDC/1A
Switching Time	Up to 4 msec
Power Requirements	11 - 15 VDC @ 650mA
Operating Temperature	-30°C to +85°C (-22°F to +185°F)
Dimensions (w/o connectors)	11.6"(295 mm) x 5.2"(132 mm) x 1.05"(27 mm)

* measured as per RS-250C @ 1km, 62.5μ cable

Note: The specifications are subject to change without notice.



Elcommtech Corp. 2620 Ocean Parkway, Suite 4H, Brooklyn, NY 11235
 Tel (718) 743-2869 • Fax (718)648-3642 • E-mail sales@elcommtech.com
<http://www.elcommtech.com>