

ECT3340T



Single Channel Single Fiber HD-SDI, SDI and ASI Auto-Sensing Fiber Optic Transmitter Card.

Video specs

Video Format: BNC Equalised Input
Video Compliance: SMPTE 292,
SMPTE 259M, DVB-ASI
Loop Out: Active Loopout
Loop Out Connector: BNC
Reclocked
O/P @ 800mV p-p
Loop Out Format: SMPTE 292,
SMPTE 259M, DVB-ASI

General Specs

Depth: 60mm
Width: 20mm 4TE
Height: 100mm (3RU)
Weight: 100g
Operating Temperature: -30 C to +70 C
MTTF @60°C: 69x10E5 hours
Power Supply: 5.8V DC @ 420mA
Signal Detect: LED On for loss of Signal

Audio/Data Specs

Passes Embedded Audio

Optical Specs

Singlemode
Optical Wavelength: 1310nm
Optical Performance: Output Power
typical -6dB
Optical Connectors: FC/PC, ST, SC

Options/ Ordering Information

ECT3340T-M-13 Multimode 1310nm
ECT3340T-S-13 Singlemode 1310nm
ECT3340T-S-13-L Singlemode Extended
Range
1310nm
ECT3340T-S-15 Singlemode 1550nm
ECT3340T-S-15-L Singlemode Extended
Range
1550nm
ECT3340T-CWDM ITU Grid CWDM
Wavelengths

