


ECT400-AS FOUR CHANNEL ANALOG SIGNAL FM OPTICAL LINK



The ECT400-AS FM system provides high performance link for unidirectional transmission of various analog signals over four, two or one a fiber optic cable. The ECT400-AS FM transmitter/receiver is fully compatible with ECT100-AS & ECT200-AS type systems allowing for mixed configurations when required. The ECT400-AS utilizes wideband linear frequency modulation/demodulation and very low noise transmission technology to assure high quality and stability.

FEATURES

- ❑ Wideband FM Transmitting/Receiving Technology
- ❑ Universal Balanced/Unbalanced Input for Transmitter
- ❑ Supports Transmission of Various Analog Signals such as: Video HDTV Tri-Level Sync, T1/E1, RF/IF, Timing, Telemetry Signals and more
- ❑ Multimode and Single Mode Versions
- ❑ Four, Two and One Fiber Configurations
- ❑ High Accuracy In/Out Signal Transmission with No Adjustments
- ❑ Signal Status Indicators

Operating Wavelength	850 nm	1300 nm	1310/1550 nm
Optical Core Diameter	50μ/62.5μ		8/10μ
Optical Power Source	VCSEL	LED	Laser
Optical Power Output*	-3 dBm	-14 dBm	-3 dBm
Receiver Sensitivity:			
Standard version	-28 dBm	-32 dBm	-34 dBm
Standard version**	-27 dBm	-31 dBm	-33 dBm
Optical Connectors	SC, ST		FC, SC, ST

* with +/- 1 dBm variation; higher power laser sources are available per special request;

** for two fiber configurations.

Signal Bandwidth @ 2dB	10 Hz - 26 MHz
Input Impedance (TX)	50, 75, 100 Ohm, Custom universal: balanced or unbalanced; up to 1 MOhm – unbalanced
Output Load Impedance (RX)	50, 75, 100 Ohm, Custom
Input/Output Signal Level:	
Option 1	0 to +/- 2 V @ 50 Ohm
Option 2	0 to +/- 2.5 V @ 75, 100 Ohm, Custom
Signal Transfer Accuracy	< 5%
Signal-to-Noise Ratio*	64 dB
Input/Output Connector	BNC
Power Requirements:	
Transmitter Card/Module	11 - 15 VDC @ 0.3 A
Receiver Card/Module	11 - 15 VDC @ 0.5 A
Operating Temperature	-20°C to +60°C (-4°F to +140°F)
Dimensions:	11.6"(295 mm) x 5.2"(132 mm) x 1.05"(27 mm)

* measured with 1km optical cable.



ECT400 SERIES

ORDERING INFORMATION

400E-AST/I -MYZ – transmitter module

400E-ASR/I-MYZ – receiver module

400E-AST/I -CYZ – transmitter card*

400E-ASR/I -CYZ – receiver card*

- E** = **M** for multimode 850 nm
= **M(13)** for multimode 1300 nm
= **M(8.5/13)** for multimode 850/1300 nm with WDM
= **S** for single mode receiver or 1310 nm transmitter
= **SP** for single mode high power (≥ 0 dBm) 1310 nm transmitter
= **S(15)** for single mode 1550 nm transmitter
= **S(13/15)** for single mode 1310/1550 nm with WDM
= **S(15)P** for single mode high power (≥ 0 dBm) 1550 nm transmitter
- I** = **50, 75, 100 Ohm, Custom** for input/output impedance
- Y** = **4, 2**** for number of fiber
- Z** = **FC, SC, ST** for optical connectors

**compatible with USR type chassis;*

***configuration with WDM optical setup;*



Elcommtech Corp. 2620 Ocean Parkway, Suite 4H, Brooklyn, NY 11235
Tel (718) 743-2869 • Fax (718)648-3642 • E-mail sales@elcommtech.com
<http://www.elcommtech.com>