

## ECT011 ONE / TWO CHANNEL TTL/CMOS DATA OPTICAL LINK



### FEATURES

- ❑ High Speed Duplex Data Transmission, DC – 26 Mb/sec
- ❑ Multimode and Singlemode Versions
- ❑ Isolates EMI, RFI, Ground Loops
- ❑ Surface Mount Technology
- ❑ Power and Signal Status Indicators
- ❑ 12V AC/DC or 24VAC Power Supply

ECT011 system provides one or two channel duplex high performance link for bi-directional transmitting TTL data signals over a fiber optic cable. The system features quality transmission of data signals with data rates DC – 26 Mb/sec. ECT011 utilizes high-speed frequency modulation and very low noise transmission technology to assure high accuracy and stability.

Operating Wavelength	850 nm	1300 nm	1310/1550nm
Optical Core Diameter	50µ/62.5µ		8/10µ
Optical Power Source	VCSEL	LED	Laser
Optical Power Output*	-3 dBm	-14 dBm	-4 dBm
Receiver Sensitivity	-30 dBm	-34 dBm	-36 dBm
Receiver Sensitivity**	-29 dBm	-33 dBm	-35 dBm
Optical Connectors	ST, SC		ST, SC, FC

\* with +/- 1 dBm variation; higher power laser sources are available per special request;  
 \*\* for configurations with internal WDM.

### ORDERING INFORMATION

011E-N/DX-XYZ

- E** = **M** for multimode
- = **M(13)** for multimode 1300nm
- = **S** for single mode receiver or 1310nm transmitter
- = **SP** for high power (0 dBm) 1310nm transmitter option
- = **S(15)** for single mode 1550nm transmitter
- = **S(15)P** for high power (0 dBm) 1550nm transmitter option
- = **SD, SPD, S(15)D, S(15)PD** for DFB lasers option
- N** = **2** for 2 ch. card-module or rack card\*
- X** = **M** for standalone module
- = **C** for rack card\*
- Y** = **1, 2** number of fibers for standalone module
- = **2, 4** number of fibers for rack card
- Z** = **ST, SC, FC** for optical connectors

\*compatible with USR type chassis

<b>Channel Capacity</b>	1Ch. - for standalone module 2Ch. - for rack card or standalone card-module
<b>Data Interface</b>	TTL, CMOS
<b>Data Rate</b>	DC – 26 Mb/sec
<b>Data Input Impedance</b>	10K unbalanced
<b>Power Requirements:</b>	
<b>1Ch. Module</b>	11 - 14 VAC/VDC @ 200 mA 21 - 27 VAC @ 150 mA
<b>2Ch. Card / Module</b>	11 - 14 VDC @ 400 mA
<b>Operating Temperature</b>	-30°C to +70°C (-22°F to +158°F)
<b>Dimensions:</b>	
<b>1Ch. Module</b>	6.86"(172mm) x 4.95"(126mm) x 1.4"(36mm)
<b>2Ch. Card / Module (w/o connectors)</b>	11.6"(270mm) x 5.2"(132mm) x 1.05"(27mm)
<b>2Ch. Card / Module (with connectors)</b>	12.5"(318mm) x 5.2"(133mm) x 1.05"(27mm)

**Note:** The specifications are subject to change without notice.



Elcommtech Corp. 2620 Ocean Parkway, Suite 4H, Brooklyn, NY 11235  
 Tel (718) 743-2869 • Fax (718)648-3642 • E-mail [sales@elcommtech.com](mailto:sales@elcommtech.com)  
<http://www.elcommtech.com>