


ECT100 SINGLE CHANNEL VIDEO FM OPTICAL LINK



FEATURES

- ❑ CCTV Professional Video Quality
- ❑ Balanced Video Input
- ❑ Compatible with NTSC, PAL and SECAM Transmission
- ❑ Multimode and Single Mode Versions
- ❑ Power and Signal Status Indicators



The ECT100 system provides high performance link for unidirectional transmission of composite video signal over a fiber optic cable. The system features CCTV professional video quality and guarantees quality transmission of video signals with maximum bandwidth up to 16 MHz.

The ECT100 transmitters/receivers are fully compatible with any ECT200 or ECT400 type systems allowing for mixed configurations when required.

The ECT100 utilizes linear frequency modulation and very low noise transmission technology to assure high quality and stability.

Operating Wavelength	850 nm	1300 nm	1310/1550nm
Optical Core Diameter	50μ/62.5μ		8/10μ
Optical Power Source	VCSEL	LED	Laser
Optical Power Output*	-7 dBm	-14 dBm	-8 dBm
Receiver Sensitivity	-30 dBm	-34 dBm	-37 dBm
Optical Connectors	ST, SC		FC, ST, SC

* with +/- 1 dBm variation; higher power laser sources are available per special request.

Video Bandwidth @ 2 dB	10Hz - 16 MHz
Video Input	75 Ohm universal: balanced or unbalanced
Video Input/Output Level	NTSC: 1.0 V p-p, PAL: 1.3 V p-p
Signal-to-Noise Ratio	68 dB*
Differential Gain	< 3%
Differential Phase	< 3°
Field Tilt	< 1 %
Luminance Non-Linearity	< 3%
Power Requirements	11 - 14 VDC @ 150mA, 21 - 27 VAC @ 100mA
Operating Temperature	-30°C to +70°C (-22°F to +158°F)
Dimensions:	
Transmitter**	3.20"(81mm) x 3.72"(95mm) x 1.1"(28mm)
Receiver**	4.17"(106mm) x 3.65"(93mm) x 1.1"(28mm)

*measured as per RS-250C @ 1km, 62.5μ cable;

**measured without optical & power connectors.



ECT100 SERIES

ORDERING INFORMATION

100E-VT-M1Z – Video transmitter module

100E-VR-M1Z – Video receiver module

- E = **M** for multimode 850 nm
 - = **M(13)** for multimode 1300 nm
 - = **S** for single mode receiver and 1310 nm transmitter
 - = **SP** for single mode high power (≥ 0 dBm) 1310 nm transmitter
 - = **S(15)** for single mode 1550 nm transmitter
 - = **S(15)P** for single mode high power (≥ 0 dBm) 1550 nm transmitter
- Z** = **FC**, **ST**, **SC** for optical connectors

Note: The specifications are subject to change without notice.



Elcommtech Corp. 2620 Ocean Parkway, Suite 4H, Brooklyn, NY 11235
Tel (718) 743-2869 • Fax (718)648-3642 • E-mail sales@elcommtech.com
<http://www.elcommtech.com>

© 2016 Elcommtech Corp. All rights reserved