

ECT100 SERIES

ECT155 FM VIDEO WITH 2 DUPLEX RS-232 DATA CHANNELS



Video	Data
1	2
→	↔

ECT155 system provides high performance link for transmitting unidirectional composite video channel along with RS-485 data channel over one or two fibers. The system features near broadcast video quality and high speed RS-485 data transfer capability. ECT155 utilizes linear frequency modulation and very low noise transmission technology to assure high quality and stability.

ORDERING INFORMATION

155E-VT/DX-MYZ – video Tx/RS-485 data TRx module
 155E-VR/DX-MYZ – video Rx/RS-485 data TRx module
 Tx - transmitter, Rx – receiver, TRx - transceiver

E = M for multimode
 = M(13) for multimode 1300nm
 = S for singlemode 1310nm
 = S(15) for singlemode 1550nm

Y = 1 for single fiber system
 = 2 for dual fiber system

Z = ST, FC, SC for optical connectors

FEATURES

- ❑ Near Broadcast Video Quality
- ❑ Compatible with NTSC, PAL and SECAM Transmission
- ❑ High Speed RS-485 Data Port
- ❑ Multimode and Singlemode Versions
- ❑ Power and Signal Status Indicators

Operating Wavelength	850 nm	1300 nm	1310/1550nm
Optical Core Diameter	50μ/62.5μ		8/10μ
Optical Power Source	VCSEL	LED	Laser
Optical Power Output*	-8 dBm	-14 dBm	-8 dBm
Receiver Sensitivity	-32 dBm	-34 dBm	-35 dBm
Receiver Sensitivity**	-30 dBm	-32 dBm	-33 dBm
Optical Connectors	ST, SC		FC, ST, SC

* with +/- 1 dBm variation

** for one-fiber configuration with internal WDM

Video Bandwidth @1dB	7 MHz
Video Input	75Ω balanced
Video Output	75Ω unbalanced
Video Input/Output Level	NTSC: 1.0 V p-p, PAL: 1.3 V p-p
Signal-to-Noise Ratio	70 dB*
Differential Gain	< 2 %
Differential Phase	< 2 °
Field Tilt	< 0.5 %
Luminance Non-Linearity	< 1.5%
Chrominance/	< 30ns
Luminance Delay	
Data Interface	RS-485
Data Rate	Up to 200 Kb/s
Bit Error Rate	10 ⁻⁹
Power Requirements	12 VAC/VDC @ 300mA 24VAC @ 200mA
Operating Temperature	-30°C to +65°C (-22°F to +149°F)
Module Dimensions	6.7"(170mm) x 4.95"(126mm) x 1.32"(34mm)

* measured as per RS-250C @ 1km, 62.5μ cable



Elcommtech Corp. 2620 Ocean Parkway, Suite 4H, Brooklyn, NY 11235
 Tel (718) 743-2869 • Fax (718)648-3642 • E-mail contact@elcommtech.com
<http://www.elcommtech.com>