

ECT200 SERIES

ECT200-L DUAL CHANNEL VIDEO FM OPTICAL LINK WITH UP TO 136 km/85 mi RANGE



Video
2 →
1 ↔

FEATURES

- ❑ CCTV Professional Video Quality
- ❑ Balanced Video Input
- ❑ Compatible with NTSC, PAL and SECAM Transmission
- ❑ Two Video Channels per Standalone Module
- ❑ Operating Range Up to 136 km / 85 miles
- ❑ Power and Signal Status Indicators

Configuration	2 Fiber	1 Fiber
Operating Wavelength	1550 nm	1530/1570 nm
Optical Core Diameter	8/10μ	
Optical Power Source	DFB Laser	
Optical Power Output	0 (+/- 0.5) dBm	
Receiver Sensitivity	-45 dBm	-44 dBm
Optical Connectors	ST, SC, FC	

ECT200-L system provides high performance link for transmitting of two composite video signals over one or two fiber optic cables. The system features CCTV professional video quality and guarantees quality transmission of video signals with maximum bandwidth up to 16 MHz.

All ECT200-L transmitter/receiver cards are fully compatible with any ECT100-L and ECT400-L type systems allowing for mixed configurations when required.

ECT200-L utilizes linear frequency modulation and very low noise transmission technology to assure high quality and stability.

Video Bandwidth @ 2dB	10 Hz - 16 MHz
Video Input Impedance	75 Ohm universal: balanced or unbalanced
Video Input Level	NTSC: 1.0 V p-p, PAL: 1.3 V p-p
Signal-to-Noise Ratio*	64 dB
Differential Gain*	< 3 %
Differential Phase*	< 3 °
Field Tilt	< 1 %
Luminance Non-Linearity	< 3 %
Operating Temperature	-30°C to +70°C (-22°F to +158°F)
Power:	
Option 1	6 - 7 VDC @ 0.4 A
Option 2	11 - 15 VDC @ 0.25 A

*measured with 1km for single mode optical cable and 10 dBm optical attenuation.



Elcommtech Corp. 2620 Ocean Parkway, Suite 4H, Brooklyn, NY 11235
 Tel (718) 743-2869 • Fax (718)648-3642 • E-mail sales@elcommtech.com
<http://www.elcommtech.com>

ECT200 SERIES

ORDERING INFORMATION

200S-VT-M2Z-L – transmitter module 1550 nm / 2 fiber
200S-VT -M1Z-L – transmitter module 1530 & 1570 nm / 1 fiber

200S-VR-M2Z-L – receiver module 1260 – 1620 nm / 2 fiber
200S-VR-M1Z-L – receiver module 1530 & 1570 nm / 1 fiber

200S-VX-M2Z-L – transceiver module 1550 nm / 2 fiber
200S(15.3)-VX-M1Z-L – transceiver module / 1 fiber: 1530 nm/TX & 1570 nm/RX
200S(15.7)-VX-M1Z-L – transceiver module / 1 fiber: 1570 nm/TX & 1530 nm/RX

Z = **FC, ST, SC** for optical connectors



Elcommtech Corp. 2620 Ocean Parkway, Suite 4H, Brooklyn, NY 11235
Tel (718) 743-2869 • Fax (718)648-3642 • E-mail sales@elcommtech.com
<http://www.elcommtech.com>