

ECT244

DUAL VIDEO WITH FOUR DUPLEX RS-422 DATA CHANNELS FM OPTICAL RECEIVER



Video	Data
2	4
→	↔

ECT244 system provides high performance link for receiving of two unidirectional composite video channels along with four bi-directional RS-422 data channels over two or four fibers. The system features CCTV professional video quality and high speed RS-422 data transfer capability. ECT244 utilizes linear frequency demodulation and very low noise reception technology to assure high quality and stability.

ORDERING INFORMATION

244E-VR/DX-CYZ – 2 x Video Rx/RS-422 data TRX card
 244E-VR/DX-MYZ – 2 x Video Rx/RS-422 data TRX module
 RX – receiver, TRX - transceiver

- E = M for multimode 850 nm/TX
- = M(13) for multimode 1300 nm/TX
- = S for single mode 1310nm/TX
- = S(15) for single mode 1550nm/TX
- Y = 2 for single fiber system (1 fiber per channel)
- = 4 for dual fiber system (2 fiber per channel)
- Z = ST, SC, FC for optical connectors

FEATURES

- ❑ CCTV Professional Video Quality
- ❑ Compatible with NTSC, PAL and SECAM Transmission
- ❑ High Speed Duplex RS-422 Data Ports
- ❑ Multimode and Singlemode Versions
- ❑ Power and Signal Status Indicators

Operating Wavelength	850 nm	1300 nm	1310/1550 nm
Optical Core Diameter	50µ/62.5µ		8/10µ
Optical Power Source	VCSEL	LED	Laser
Optical Power Output*	-7 dBm	-14 dBm	-8 dBm
Video & Data Receiver Sensitivity	-30 dBm	-34 dBm	-36 dBm
Video & Data Receiver Sensitivity**	-29 dBm	-33 dBm	-35 dBm
Optical Connectors	ST, SC		FC, ST, SC

* with +/- 1 dBm variation; higher power laser sources are available per special request;

** for one-fiber configuration with internal WDM

Video Bandwidth @ 3 dB	7 MHz
Video Output	75 Ohm unbalanced
Video Output Level	NTSC: 1.0 V p., PAL: 1.3 V p. (+/-10%)
Signal-to-Noise Ratio	62 dB*
Differential Gain	< 4 %
Differential Phase	< 4 °
Field Tilt	< 2 %
Luminance Non-Linearity	< 4 %
Data Interface	RS-422
Data Rate	Up to 200 Kb/s
Bit Error Rate	10 ⁻⁹
Power Requirements	11 - 15 VDC @ 500mA
Operating Temperature	-30°C to +85°C (-22°F to +185°F)
Dimensions (w/o connectors)	11.6''(295 mm) x 5.2''(132 mm) x 1.05''(27 mm)

* measured as per RS-250C @ 1km, 62.5µ cable

Note: The specifications are subject to change without notice.



Elcommtech Corp. 2620 Ocean Parkway, Suite 4H, Brooklyn, NY 11235
 Tel (718) 743-2869 • Fax (718)648-3642 • E-mail sales@elcommtech.com
<http://www.elcommtech.com>