

ECT3600T



12-Channel Balanced Analog Audio Multiplexing Transmitter 1RU Subrack including Power Supply.

Audio/Data Specs

12 x Balanced 600R Audio
Audio/Data Format: Input Level 18dBu
ref. 1mW into 600R,
System Gain 0dB nom +/-0.5dB,
Bandwidth +/-0.25dB <20Hz to >20kHz,
Noise ref. full scale <-90dB p-p weighted
Audio Impedance: Input Impedance 100K
Audio/Data Connector: XLR

Optical Specs

Singlemode
Optical Wavelength: 1310nm
Optical Performance: Output Power typical -6dB
Optical Connectors: FC/PC, ST, SC

General Specs

Depth: 250mm
Width: 19in.
Height: 1RU
Weight: 2kg
Operating Temperature: -30 C to +70 C
MTTF @60°C: 69x10E5 hours
Power Supply: 85-270V AC 47-63Hz
Signal Detect: Power On LED, Oscillator Lock LED

Options/ Ordering Information

ECT3600T-M-13-1RU Multimode 1310nm Transmitter
ECT3600T-S-1311RU Singlemode 1310nm Transmitter
ECT3600T-S-15-1RU Singlemode 1550nm Transmitter
ECT3600T-S-CWDM-1RU Singlemode CWDM Tuned Laser Option Transmitter.

